

SAFETY DATA SHEET

PRODUCT NAME: **ACRYLIC COLORS**

1 – IDENTIFICATION OF MATERIAL AND SUPPLIER

SUPPLIER: _____

ADDRESS: _____

TELEPHONE: _____

FACSIMILIE: _____

EMERGENCY: _____

WEB SITE: _____

E-MAIL: _____

SYNONOMYS: **CHRYSANTHOS ACRYLIC COLORS**

USES: **ACRYLIC PAINTS**

ISSUED DATE: Tuesday, 1 May 2018

2 – HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO CRITERIA OF NOHSC

No adverse side effects are expected if the product is handled in accordance with this safety data sheet and product label. Symptoms of effects may occur if the product is mishandled.

SILICA

Crystalline Silica may be present. Crystalline silica may cause irritation to eyes, skin and the respiratory tract. Prolonged or repeated inhalation of silica, in excess of TLV, may lead to delayed lung injury (silicosis). This material is listed as a possible carcinogen.

POLYETHYLENE GLYCOL

May cause mild irritation to skin and eyes. Routes of Entry: Dermal, Ingestion, absorption through the skin negligible. Inhalation only if sprayed.

GHS LABEL ELEMENTS:

HAZARD STATEMENTS: None allocated

PRECAUTIONARY STATEMENTS: None allocated

NOT CLASSIFIED AS DANGEROUS GOODS BY THE CRITERIA OF THE ADG CODE

UN NUMBER: None allocated

DG CODE: None allocated

PACKING GROUP: None allocated

SUBSIDURARY RISK: None allocated

HAZCHEM CODE: None allocated

3 – COMPOSITION / INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

PRODUCT NAME: ACRYLIC COLORS

ENTITY	CAS NO	CLASSIFICATION	%
ACRYLIC CO-POLYMER	Proprietary	N/A	< 25%
FUMED SILICA	69012-64-2	N/A	< 4%
DIATOMACEOUS EARTH	68855-54-9	STOT RE 2 H373 (lungs)	< 20%
POLYETHYLENE	25322-68-3	N/A	< 2%
GLYCOL			
PIGMENTS	Various	N/A	< 20%
THICKENER	N/A	N/A	< 1%
COALESCING AGENT	25265-77-4	N/A	< 2%
DISPERSANT	N/A	N/A	< 2%
ANTIFOAM	N/A	N/A	< 1%
SURFACTANT	N/A	N/A	< 1%
PRESERVATIVE	N/A	N/A	< 1%
PH STABILIZER	N/A	N/A	< 1%
WATER	N/A	N/A	< 45%

4 – FIRST AID MEASURES

EYE:	May cause irritation. Flush eyes with large quantities of water for at least 15 minutes. If irritation persists after washing, contact a doctor.
INHALED:	May cause irritation. Remove from exposure.
SKIN:	May cause irritation. Wash skin with soap and water.
SWALLOWED:	Immediately rinse the mouth. Do not induce vomiting. Seek medical advice if symptoms persist..
ADVICE TO DOCTOR:	Treat symptomatically.

5 – FIRE FIGHTING MEASURES

FLAMMABILITY:	Non Flammable.
FIRE & EXPLOSION:	No fire or explosion hazard exists.
EXTINGUISHING:	Use an extinguishing agent suitable for the surrounding fire.
HAZCHEM CODE:	None allocated.

6 – ACCIDENTAL RELEASE MEASURES

SPILLAGE:	Use personal protection equipment. Contain spillage. Uncontaminated material may be recovered and re-used. Contaminated material to be covered / absorbed with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.
------------------	---

7 – STORAGE AND HANDLING

SAFETY DATA SHEET

PRODUCT NAME: ACRYLIC COLORS

STORAGE: Store in a cool, dry, well ventilated area, removed from oxidizing agents, acids and foodstuffs. Ensure that containers are adequately labeled, protected from physical damage, and sealed when not in use.

HANDLING: Before using carefully read the product label. Use of safe practices is recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION


EXPOSURE STANDARDS:

INGREDIENT	TWA		STEL		ACGIH TLV	
	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
DIATOMACEOUS EARTH	-	-	-	-	-	.05

BIOLOGICAL LIMITS: No biological limits allocated.

ENGINEERING CONTROLS: Avoid inhalation when spraying. Use in well ventilated area. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain vapor levels below the recommended exposure standard.

PPE



Eye / Face Wear appropriate eye protection / safety glasses to keep mist out of eyes if spray application is used.

Hands Not normally needed.

Body Wear appropriate clean, protective clothing such as, but not limited to, overalls, smocks, and aprons.

Respiratory Use a NIOSH approved respirator if spray application is used.

9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Viscous Colored liquid
ODOUR:	Negligible
BOILING POINT:	100°C
MELTING POINT:	N/A
VAPOUR PRESSURE:	NOT AVAILABLE
SPECIFIC GRAVITY:	1.2 – 1.45 @ 25°C
FLASH POINT:	NOT RELEVANT
FLAMMABILITY LIMITS:	NON FLAMMABLE
SOLUBILITY IN WATER:	MISCIBLE
VISCOSITY:	No data
pH:	7.0 – 8.5
% VOLATILES	N/A
EVAPORATION RATE	NOT AVAILABLE
UPPER EXPLOSION LIMIT	NOT RELEVANT
LOWER EXPLOSION LIMIT	NOT RELEVANT

10 – STABILITY AND REACTIVITY

REACTIVITY: None known.

SAFETY DATA SHEET

PRODUCT NAME: ACRYLIC COLORS

CHEMICAL STABILITY: Stable.

CONDITIONS TO AVOID: Mist created from spray application. Avoid contact with incompatible substances.

INCOMPATIBLE MATERIAL: None known.

HAZARDOUS DECOMPOSITION: None known.

HAZARDOUS REACTIONS: None known.

11 – TOXICOLOGICAL INFORMATION

HEALTH HAZARD SUMMARY: Under normal conditions of use, adverse health effects are not anticipated. Due to the form of the products and low volatility, an inhalation hazard is not anticipated unless products are sprayed.

EYE: Low irritants. Contact may result in irritation, lacrimation and redness.

INHALATION: Exposure considered unlikely. Due to the form of the products and nature of use, an inhalation hazard is not anticipated with normal use.

SKIN: Low irritants. Prolonged or repeated contact may result in mild irritation.

INGESTION: Low toxicity. Ingestion is considered unlikely due to the form of the products. However ingestion via hand-mouth transfer may result in gastrointestinal irritation, nausea and vomiting. Maintain good personal hygiene standards.

TOXICITY DATA:

QUARTZ (SILICA CRYSTALLINE) (14808-60-7)
LCLo (inhalation) 300 µg/m ³ /10 years (human)
TCLo (inhalation) 16,000,000 particles/ft ³ /8 hrs/17.9 years (human fibrosis)

12 – ECOLOGICAL INFORMATION

ENVIRONMENT: Do not release this product or chemically contaminated water containing this product into drains, soils or surface water. Make sure that water used in extinguishing any fires involving this product is disposed according to local regulations.

13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: For small amounts absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer for additional information if larger amounts are involved.

LEGISLATION: Dispose of in accordance with relevant local legislation.

14 – TRANSPORTATION

NOT CLASSIFIED AS DANGEROUS GOODS BY THE CRITERIA OF THE ADG CODE.

SAFETY DATA SHEET

PRODUCT NAME: ACRYLIC COLORS

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG/IMO)	AIR TRANSPORT (IATA/ICAO)
UN NUMBER	None Allocated	None Allocated	None Allocated
PROPER SHIPPING NAME	Water based artist and hobby acrylic paint	Water based artist and hobby acrylic paint	Water based artist and hobby acrylic paint
DG CLASS / DIVISION	None Allocated	None Allocated	None Allocated
SUBSIDIARY RISKS	None Allocated	None Allocated	None Allocated
PACKING GROUP	None Allocated	None Allocated	None Allocated
HAZCHEM CODE	None Allocated	None Allocated	None Allocated

15 – REGULATORY INFORMATION

INVENTORY LISTINGS:

AUSTRALIA:

All components are listed on AICS or are exempt.

USA:

Silica is listed on IARC, OSHA and NTP carcinogen list.

All ingredients are on TSCA inventory.

California Proposition 65 - Proposition 65: Silica (Quartz) is listed on the carcinogen list.

CANADA:

All ingredients are on DSL inventory.

WHMIS – Not controlled.

EUROPE:

All ingredients are on EC inventory.

CHEMICAL SAFETY ASSESSMENT:

EU:

Does not require a hazardous warning label according to the EU guidelines/Dangerous Chemicals Ordinance.

16 – OTHER INFORMATION

ADDITIONAL INFORMATION:

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

ABBREVIATIONS:

AICS Australian Inventory of Chemical Substances
ACGIH American Conference of Governmental Industrial Hygienists

SAFETY DATA SHEET


PRODUCT NAME: ACRYLIC COLORS

CAS #	Chemical Abstracts Service Number
CNS	Central Nervous System
EC No.	EC No – European Community Number
GHS	Globally Harmonized System
IARC	International Agency for Research on Cancer
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per cubic meter
PEL	Permissible Exposure Limit
pH	Acidity < 7 – Alkalinity > 7 measure
ppm	Parts Per Million
REACH	Regulation on Registration, Evaluation, Authorization and Restriction of Chemicals
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
TLV	Threshold Limit Value
TWA/OEL	Time Weighted Average of Occupational Exposure Limit
STEL	Short Term Exposure Limit
TSCA	Toxic Substances Control Act

REVISION HISTORY:

Revision	Description
1.0	Creation

REPORT STATUS:



The report has been by Chrysanthos Color Company Limited – China. The information provided on safety and handling represents the current knowledge at the time of writing. We should be contacted directly for further clarification regarding any aspect of the product if required.

The SDS has been prepared with all due care to include accurate and up-to-date information. We do not however provide any warranty as to accuracy or completeness. As far as lawfully possibly, Chrysanthos Color Company Limited – China accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained herein.

PREPARED BY:

Tony Crisafi
Chrysanthos Color Company Limited
2nd Floor, Building B1,
No 19 Gaoxinxishi Road,
Nanning High Tech Zone, Nanning,
Guangxi 530003, China.
Tel/Fax: +86 (771) 231 0885
Mob: +61 402 830 337
Email: info@chrysanthos.com
Web: www.chrysanthos.com

End of SDS